

## GK35-6 Sewing head with CP4900 and Pedestal

This unit, which is constituted by GK35-6 sewing head, CP4900 bags infeed device and a column, is used to close bags filled with various products e.g. foodstuff, fertilizer, feed, & chemicals. Working with various belt conveyors, it can accomplish packing operation efficiently.

- ✧ Speed: 6~12m/min, 240~600bags/h;
- ✧ Weight of the bags: 10~100kg;
- ✧ Height of bags: 400-900mm;
- ✧ Bag top folding depth: 30-60mm
- ✧ Start-stop: automatically by photoswitch;
- ✧ Thread cutter: automatically by air cylinder operated guillotine type cutter;
- ✧ Stitch length: adjustable from 6.5-11 mm, standard setting 8 mm;
- ✧ Standard needle: 80800 x 250#
- ✧ 0.37 KW for sewing head, 0.18KW for infeed;
- ✧ Net weight: about 150kg;



## LFS2500 Belt conveyor with GK35-6 and CP4900

This unit, which is constituted by GK35-6 sewing head, CP4900 bags infeed device, LFS2500 Belt conveyor and a column, is used to close bags filled with various products e.g. foodstuff, fertilizer, feed, & chemicals. It is suitable for stitching packing of paper bags woven bags after bag top folding.

- ✧ Speed: 6~12m/min, 240~600bags/h;
- ✧ Weight of the bags: 10~100kg;
- ✧ Height of bags: 400-900mm;
- ✧ Bag top folding depth: 30-60mm
- ✧ Start-stop: automatically by photoswitch;
- ✧ Thread chain cutter: automatically by air cylinder operated guillotine type cutter;
- ✧ Stitch length: adjustable from 6.5-11 mm, standard setting 8 mm;
- ✧ Standard needle: 80800×250#
- ✧ Conveyor length 2.5m; Width: 400mm
- ✧ Motor: 0.55KW for belt conveyor, 0.37 KW for sewing head, 0.18KW for infeed.



GK35-6 Sewing head with CP4900  
and Pedestal



LFS2500 Belt conveyor with GK35-6 and CP4900