## LFS Series Belt conveyor

## LFS1500 Belt conveyor with GK35-2C/GK35-6

### LFS1500 Belt conveyor with GK35-2C

This unit, which is constituted by GK35-2C sewing head, LFS1500 Belt conveyor and a column, is used to close bags filled with various products e.g. foodstuff, fertilizer, feed, & chemicals.

Simple belt conveyor, fixed column.

- ♦ Speed: 6~12m/min, 240~600bags/h;
- ♦ Weight of the bags: 10~100kg;
- ♦ Height of bags: 400-900mm;
- ♦ Start-stop: actuated by foot switch of column;
- ♦ Thread chain cutter: by continuously driven nibbler knives;
- ♦ Stitch length: adjustable from 6.5-11mm;
- ♦ Standard needle: 80800 × 200#-250#
- ♦ Conveyor length1.5m; Width: 350mm
- ♦ 0.37KW for belt conveyor, 0.37 KW for sewing head

### LFS1500 Belt conveyor with GK35-6

This unit, which is constituted by GK35-6 sewing head, LFS1500 Belt conveyor and a column, is used to close bags filled with various products e.g. foodstuff, fertilizer, feed, & chemicals.

Simple belt conveyor, fixed column.

- ♦ Speed: 6~12m/min, 240~600bags/h;
- ♦ Weight of the bags: 10~100kg;
- ♦ Height of bags: 400-900mm;
- ♦ Start-stop: automatically by photoswitch;
- Thread chain cutter: automatically by air cylinder operated guillotine type cutter;
- ♦ Stitch length: adjustable from 6.5-11 mm, standard setting 8 mm;
- ♦ Standard needle: 80800 × 200#-250#
- ♦ Conveyor length1.5m; Width: 350mm
- ♦ 0.37KW for belt conveyor, 0.37 KW for sewing head

## LFS2000 Belt conveyor with GK35-2C/GK35-6

#### LFS2000 Belt conveyor with GK35-2C

This unit, which is constituted by GK35-2C sewing head, LFS2000 Belt conveyor and a column, is used to close bags filled with various products e.g. foodstuff, fertilizer, feed, & chemicals.

Liftable belt conveyor, fixed column.

- ♦ Speed: 6~12m/min, 240~600bags/h;
- ♦ Weight of the bags: 10~100kg;
- ♦ Height of bags: 400-900mm;
- ♦ Start-stop: actuated by foot switch of column;



- ♦ Thread chain cutter: by continuously driven nibbler knives;
- ♦ Stitch length: adjustable from 6.5-11 mm;
- ♦ Standard needle: 80800 × 200#-250#
- ♦ Conveyor length2.0m; Width: 400mm
- ♦ 0.55KW for belt conveyor, 0.37 KW for sewing head

### LFS2000 Belt conveyor with GK35-6

This unit, which is constituted by GK35-6 sewing head, LFS2000 Belt conveyor and a column, is used to close bags filled with various products e.g. foodstuff, fertilizer, feed, & chemicals.

Liftable belt conveyor, fixed column.

- ♦ Speed: 6~12m/min, 240~600bags/h;
- ♦ Weight of the bags: 10~100kg;
- ♦ Height of bags: 400-900mm;
- ♦ Start-stop: automatically by photoswitch;
- Thread chain cutter: automatically by air cylinder operated guillotine type cutter;
- ♦ Stitch length: adjustable from 6.5-11 mm;
- ♦ Standard needle: 80800 × 200#-250#
- ♦ Conveyor length2.0m; Width: 400mm
- ♦ 0.55KW for belt conveyor, 0.37 KW for sewing head



# LFS2500 Belt conveyor with GK35-8/GK35-8A

### LFS2500 Belt conveyor with GK35-8

This unit, which is constituted by GK35-8 double needles sewing head, LFS2500 Belt conveyor and a column, is used to close bags filled with various products e.g. foodstuff, fertilizer, feed, & chemicals.

Moveable belt conveyor, Moveable column.

- ♦ Speed: 6~12m/min, 240~600bags/h;
- ♦ Weight of the bags: 10~100kg;
- ♦ Height of bags: 400-900mm;
- ♦ Start-stop: actuated by foot switch of column;
- ♦ Thread cutter: by continuously driven nibbler knives;
- ♦ Stitch length: adjustable from 6.5-11 mm;
- ♦ Needle distance: 6 mm, staggered
- ♦ Standard needle: 80800 × 200#-250#
- ♦ Conveyor length2.5m; Width: 400mm
- ♦ 0.55KW for belt conveyor, 0.37 KW for sewing head

### LFS2500 Belt conveyor with GK35-8A

This unit, which is constituted by GK35-8A double needles automatic sewing head, LFS2500 Belt conveyor and a column, is used to close bags filled with various products e.g. foodstuff, fertilizer, feed, & chemicals.



Moveable belt conveyor, Moveable column.

- ♦ Speed: 6~12m/min, 240~600bags/h;
- ♦ Weight of the bags: 10~100kg;
- ♦ Height of bags: 400-900mm;
- ♦ Start-stop: automatically by photoswitch;
- ♦ Thread chain cutter: automatically by air cylinder operated guillotine type cutter;
- ♦ Stitch length: adjustable from 6.5-11 mm, standard setting 8 mm;
- ♦ Needle distance: 6 mm, staggered
- ♦ Standard needle: 80800 × 200#-250#
- ♦ Conveyor length2.5m; Width: 400mm
- ♦ 0.55KW for belt conveyor, 0.37 KW for sewing head

### LFS3000 Belt conveyor with GK35-2C/GK35-6

### LFS3000 Belt conveyor with GK35-2C

This unit, which is constituted by GK35-2C sewing head, LFS3000 Belt conveyor and a column, is used to close bags filled with various products e.g. foodstuff, fertilizer, feed, & chemicals.

Liftable belt conveyor, fixed column

- ♦ Start-stop: actuated by foot switch of column;
- ♦ Thread chain cutter: by continuously driven nibbler knives;
- ♦ Stitch length: adjustable from 6.5-11 mm;
- ♦ Standard needle: 80800 × 200#-250#
- ♦ Speed: 6~12m/min, 240~600bags/h;
- ♦ Weight of the bags: 10~100kg;
- ♦ Height of bags: 400-900mm;
- ♦ Conveyor length: 3.0m; Width: 400mm
- ♦ 0.55KW for belt conveyor, 0.37 KW for sewing head

### LFS2500 Belt conveyor with GK35-6

This unit, which is constituted by GK35-6 sewing head, LFS3000 Belt conveyor and a column, is used to close bags filled with various products e.g. foodstuff, fertilizer, feed, & chemicals.

Liftable belt conveyor, fixed column.

- ♦ Start-stop: automatically by photoswitch;
- ♦ Thread chain cutter: automatically by air cylinder operated guillotine type cutter;
- ♦ Stitch length: adjustable from 6.5-11 mm;
- ♦ Standard needle: 80800 × 200#-250#
- ♦ Speed: 6~12m/min, 240~600bags/h;
- ♦ Weight of the bags: 10~100kg;
- ♦ Height of bags: 400-900mm;
- ♦ Conveyor length: 3.0m; Width: 400mm
- ♦ 0.55KW for belt conveyor, 0.37 KW for sewing head

HeBei QingGong sewing machine Co., Ltd Address: Qing county, Hebei province, 062650, China

TEL:0086-15222588537 Fax:0086-3174262868 Web: <a href="https://www.QingGongSewing.com">www.QingGongSewing.com</a> Email: <a href="https://ggfr1996@163.com">ggfr1996@163.com</a>